Condensate Treater

FALSKEN
WATER SYSTEMS, INC.
Quality Water Treatment Equipment

The Condensate Treater is an in-line cartridge containing a blend of media designed to neutralize the acidic condensation discharge from the high efficiency, condensing tankless water heaters.

Condensation is high purity water which is naturally acidic. This unit provides an environmentally responsible solution when local codes require neutralization of the condensate prior to discharge to a drain, septic system, sewer or landscaping.

It also offers the consumer a way to prevent premature deterioration or damage to metal pipe, ABS pipe, septic tanks, plants, concrete and other materials that may be affected by contact with the untreated condensate discharge.

Features

- Simple, effective and environmentally friendly
- Comes complete with fittings for most tankless water heater configurations
- Compact & visually pleasing design
- Replace annually or when the pH moves below 6.0
- Follow local code requirements for the discharge of condensate
- Attaches directly to the heater or remotely
- For single heater residential or light commercial applications

Made in the USA

FAL-HTILCN-12

Specifications

- 12" long x 2½" round
- ⅜" FPT inlet & outlet
- Flow 3.8 gph gravity flow (14.4 L/Hour)
- Temperature range 40-100º F (4.4–37.8 c)
- Max pressure 125 psi (8.6 bars)
- Case Quantity: 12
- Case Size: 14" x 12" x 8½"
- Case Weight: 20 lbs.
- Individual Unit Weight: 1.7 lbs.
- Install in a vertical or downward position

2½"

12"

Components Included

⅜" MPT x ½" Slip

⅜" MPT x ½" FPT

⅜" MPT x ¾" Barb

⅜" MPT x ½" Barb

Mounting Clip